

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
13 May 2004 (13.05.2004)

PCT

(10) International Publication Number  
**WO 2004/040505 A1**

- (51) International Patent Classification<sup>7</sup>: **G06K 19/06**, **G07D 7/02**
- (21) International Application Number:  
PCT/GB2003/004676
- (22) International Filing Date: 30 October 2003 (30.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0225290.6 30 October 2002 (30.10.2002) GB
- (71) Applicant (for all designated States except US): **THE SECRETARY OF STATE FOR TRADE AND INDUSTRY** [GB/GB]; 1 Victoria Street, London SW1 0ET (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **MENDELS, David, Alexis** [FR/GB]; National Physical Laboratory, Queens Road, Teddington, Middlesex TW11 0LW (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IDENTIFICATION DEVICE, ANTI-COUNTERFEITING APPARATUS AND METHOD



(57) Abstract: The preferred embodiment provides a 3D nanometer scale data encryption key. It consists in using 3D polymer patterns on silicon substrates as evolved, tri-dimensional barcodes. It provides several possible degrees of encryption which, together with the high technology involved, makes it virtually impossible to counterfeit. There is described the basic geometry, the process, the coding principles through such structures, and the reading principles. The preferred geometry is that of an array of lines, similar to a barcode when seen from above, with the difference that lines have dimensions in the tens of nanometer range. These lines are preferably made of a cross-linked, modified Poly(methyl methacrylate). Cross-linking by ultra-violet light gives them an exceptional mechanical durability for structures of this size.